

Action Schema Attribute Reference

FOX:Schema:ACTION REFERENCE

- fox:actionClass
- fox:actionSpell
- fox:actionSpellOk
- fox:actionStyle
- fox:confirm
- fox:defaultAction
- fox:displayOrder
- fox:image
- fox:prompt
- fox:ro
- fox:run
- fox:widget

FOX:Schema:actionClass

fox:actionClass

Description

```
fox:actionClass="Literal String"
```

Assigns one or more CSS classes to an action's widget

Note: Some widget types (e.g. button) will overwrite the class attribute, so setting an actionClass on elements with these widgets has no effect.

Values

A space-separated string of CSS classes

FOX:Schema:actionSpell

fox:actionSpell

Description

```
fox:actionSpell="XPath Boolean"
```

Specifies whether an action/phantom requires a spell check before being run.

Values

Default: false

FOX:Schema:actionSpellOk

fox:actionSpellOk

Description

```
fox:actionSpellOk="XPath String"
```

The message to display after a successful spell check. For use on phantoms or actions.

Values

Default: "Spell Checking Complete."

FOX:Schema:actionStyle

fox:actionStyle

Description

```
fox:actionStyle="Literal String"
```

Defines the style applied to an action's widget.

Values

A semi-colon (;) separated string of CSS property declarations in the form "name: value" (this is the same syntax as HTML inline styles ^[1]).

References

[1] <http://www.w3.org/TR/REC-html40/present/styles.html#h-14.2.2>

FOX:Schema:confirm

fox:confirm

Description

```
fox:confirm="XPath String"
```

Shows an OK/Cancel dialog to the user before an action is run. If the user clicks Cancel or closes the dialog, the action does not run.

Values

Message shown in dialog box.

FOX:Schema:defaultAction

fox:defaultAction

Description

```
ns:defaultAction="XPath Boolean"
```

Applied on an fm:action, if the XPath expression evaluates to true then the action becomes the 'default' action for that HTML page.

Only one action on a page may be the default at a given time.

Image actions

defaultAction works by changing the type of input generated. If the action has been marked up with the imageUrl attribute it will be generated as an image and defaultAction will not work. To get around this you can use a separate action as a 'trigger' which acts as the defaultAction and then calls your desired action. CSS can be used to place this off the screen so the functionality is transparent to the user.

FOX:Schema:displayOrder

fox:displayOrder

Description

```
fox:displayOrder="Integer"
```

FOX:Schema:image

fox:image

Description

fox:image=*Literal String*

FOX:Schema:prompt

fox:prompt

Description

```
fox:prompt="XPath String"
```

The prompt to display for this element.

Values

Default: `initCap(replace("_", " ",elementName))`

FOX:Schema:ro

fox:ro

Description

fox:ro=*XPath Boolean*

FOX:Schema:run

fox:run

Description

fox:run="*XPath Boolean*"

FOX:Schema:widget

fox:widget

Description

```
fox:widget="Literal String"
```

The widget to use to display the schema element.

Values

- alive
 - alive+
 - button
 - button+
 - cartographic
 - date
 - date+
 - datetime
 - datetime+
 - file
 - file-new
 - file-upload
 - html
 - html+
 - icon
 - iconprompt
 - input
 - input+
 - input-resizable
 - image
 - link
 - link+
 - mailto
 - mailto-btn
 - obscure
 - password
-

- print
 - radio
 - selector
 - selector+
 - static-text
 - tickbox
 - timer+
 - url
 - url-btn
-